

WOODCARE

BUTTON POLISH

A high quality polish made from Button Shellac.
Dark in colour, often used to produce antique finish or similar appearance.

Interior use only.



250mle
UN No. 1263

Barrettine

R1

SHAKE WELL

Instructions for use: Ensure all surfaces are clean, dry and free from grease and dust. Apply polish with a brush or cloth-often called a 'rubber'. Apply up to five coats, allowing to dry thoroughly between applications. After the first coat, the surface of the wood may appear roughened - lightly rub down with the finest wire wool or flour paper. The final coat can be applied using a mixture of 50/50 Methylated Spirit and Button Polish. Clean all brushes etc with Methylated Spirit.

HEALTH & SAFETY

Highly flammable liquid and vapour. • Causes serious eye irritation. • Keep out of reach of children. • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. • Wear protective gloves/protective clothing/eye protection/face protection. • Wash contaminated skin thoroughly after handling. • In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. • Store in a well-ventilated place. Keep cool. • Dispose of contents/container in accordance with national regulations.

Contains: Ethanol, Isopropanol, Butanone.

Very high: VOC content >50%
VOCs (Volatile Organic Compounds) Contribute to atmospheric pollution.

EU limit value for this product (A/h 750 g/l (2007) 750 g/l (2010)
This product contains max 614 g/l VOC



Danger



St. Ivel Way, Warmley, Bristol BS30 8TY. T: +44 (0) 117 960 0060 F: +44 (0) 117 935 2437
E: sales@barrettine.co.uk www.barrettine.co.uk