Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758



## SAFETY DATA SHEET

Zinsser Ceiling Pro 5-in-1

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- **1.1 Product identifier**
- Product name

Product type

UFI

: Zinsser Ceiling Pro 5-in-1

Product description

- : Paint : Liquid.
- : NTRQ-WCQH-6KKR-UAP1

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses				
Consumer use Industrial use Professional use				
Uses advised against	Reason			
None identified.	-			

#### 1.3 Details of the supplier of the safety data sheet

RUST-OLEUM EUROPE Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium Telephone no.: +32 (0) 13 460 200 Fax no.: +32 (0) 13 460 201

Tor Coatings Limited Unit 21, White Rose Way, Follingsby Park, Gateshead, Tyne & Wear, NE10 8YX United Kingdom Telephone no.: +44 (0) 191 4106611 Fax no.: +44 (0) 191 4920125 enquiries@tor-coatings.com

e-mail address of person : rpmeurohas@rustoleum.eu responsible for this SDS

#### **1.4 Emergency telephone number**

#### National advisory body/Poison Centre

**Supplier** 

Telephone number United Kingdom: : +44 870 8200418 / +44 2038073798 Great Britain

Hours of operation

: 24/7

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

## **SECTION 2: Hazards identification**

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
General	:	P103 - Read carefully and follow all instructions. P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	1	Not applicable.
Response	:	Not applicable.
Storage	1	Not applicable.
Disposal	1	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	EUH208 - Contains 1,2-benzisothiazol-3(2H)-one and 4,5-dichloro-2-octyl-2H- isothiazol-3-one. May produce an allergic reaction. EUH210 - Safety data sheet available on request. EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Supplemental label elements : Detergents - Regulation (EC) No 907/2006	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.

#### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do : None known. not result in classification

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### : Mixture

#### United Kingdom: Great Britain

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Date of issue/Date of revision	:07/11/2022	Date of previous iss	ue : 07/11/2022	Version : 6	2/15

Zinsser Ceiling Pro 5-in-1

SECTION 3: Compo	osition/informat	ion on i	ingredients		
1,2-benzisothiazol-3(2H)- one	REACH #: 01-2120761540-60 EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0,05	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	ATE [Oral] = 490 mg/kg ATE [Inhalation (vapours)] = 0,5 mg/l Skin Sens. 1, H317: $C \ge 0,05\%$ M [Acute] = 1	[1]
4,5-dichloro-2-octyl-2H- isothiazol-3-one	EC: 264-843-8 CAS: 64359-81-5	<0,001	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 567 mg/kg ATE [Inhalation (dusts and mists)] = 0,16 mg/l Skin Corr. 1, H314: $C \ge 5\%$ Skin Irrit. 2, H315: 0,025% $\le C < 5\%$ Eye Dam. 1, H318: $C \ge 3\%$ Eye Irrit. 2, H319: 0,025% $\le C < 3\%$ Skin Sens. 1, H317: $C \ge 0,0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Туре

[1] Substance classified with a health or environmental hazard

This mixture contains  $\geq$  1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed <u>Over-exposure signs/symptoms</u>

Date of issue/Date of revision         : 07/11/2022         Date of previous issue         : 07/11/2022         Version         : 6         3/		Date of issue/Date of revision	: 07/11/2022	Date of previous issue	:07/11/2022	Version : 6	3/15
--	--	--------------------------------	--------------	------------------------	-------------	-------------	------

SECTION 4: First aid	measures
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
4.3 Indication of any immedia	ate medical attention and special treatment needed
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
SECTION 5: Firefight	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion	: Decomposition products may include the following materials:
products	carbon dioxide carbon monoxide metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
Additional information	: No unusual hazard if involved in a fire.
SECTION 6: Acciden	

6.1 Personal precautions, pro	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and material for containment and cleaning up

Date of issue/Date of revision

## SECTION 6: Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance.

7.1 Precautions for safe ha	andling
Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

: Not available.

: Not available.

SECTION 8: Exposure controls/personal protection

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.					
8.1 Control parameters					
Occupational exposure limits					
procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance				

7.3 Specific end use(s) Recommendations

solutions

Industrial sector specific

## SECTION 8: Exposure controls/personal protection

documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Inhalation	6,81 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	1,2 mg/m³	General population	Systemic
	DNEL	Long term Dermal	0,966 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0,345 mg/ kg bw/day	General population	Systemic

#### **PNECs**

Product/ingredient name	Compartment Detail	Value	Method Detail
titanium dioxide	Fresh water	0,127 mg/l	-
	Marine	>1 mg/l	-
	Sewage Treatment	>100 mg/l	-
	Plant		
	Fresh water sediment	>1000 mg/kg	-
	Marine water sediment	>100 mg/kg	-
	Soil	100 mg/kg	-
	Marine water	0,0184 mg/l	-
	Fresh water	0,184 mg/l	-

#### 8.2 Exposure controls

Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.	;
Individual protection measu	<u>es</u>	
	· Mash hands, fare such face there will after headling chamical are due to	

Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### **Skin protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

#### **Hand protection :** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. > 8 hours (breakthrough time): nitrile rubber (0.5mm) gloves.

## **SECTION 8: Exposure controls/personal protection**

		The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt. (EN 467)
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate filter (EN 140).
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Physical state** : Liquid. Colour : White. : Not available. Odour : Not available. **Odour threshold** Melting point/freezing point : 0°C [Literature] Initial boiling point and : >100°C (>212°F) [Literature] boiling range : Non-flammable in the presence of the following materials or conditions: open Flammability (solid, gas) flames, sparks and static discharge, heat and shocks and mechanical impacts. Nonflammable, but will burn on prolonged exposure to flame or high temperature. Lower and upper explosion : Not available. limit **Flash point** : Not relevant due to nature of the product. : Not relevant due to nature of the product. Auto-ignition temperature **Decomposition temperature** : Not available. pН : 4 to 6 [Conc. (% w/w): 100%] [OECD 122] pH : Justification : Not available. Viscosity Dynamic: 2800 to 3150 mPa·s [ASTM D562 [KU]] ÷ Solubility(ies) ż Media Result cold water Soluble hot water Soluble methanol Very slightly soluble acetone Very slightly soluble Solubility in water : Not available.

9.1 Information on basic physical and chemical properties

Date of issue/Date of revision

: 07/11/2022 Date of previous issue

7/15

## **SECTION 9: Physical and chemical properties**

Partition coefficient: n-octanol/ water	1	Not applicable.
Vapour pressure	;	2,3 kPa (17,25 mm Hg) [Literature]
Evaporation rate	1	<1 (butyl acetate = 1)
Relative density	:	Not available.
Density	;	1,422 to 1,482 g/cm <sup>3</sup> [20°C (68°F)] [DIN 53217]
Vapour density	:	>1 [Air = 1]
Explosive properties	1	Not applicable.
Oxidising properties	1	Not available.
Particle characteristics		
Median particle size	1	Not applicable.

SECTION 10: Stability and reactivity		
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.	
10.2 Chemical stability	: The product is stable.	
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	: No specific data.	
10.5 Incompatible materials	: No specific data.	
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
1,2-benzisothiazol-3(2H)- one	LC50 Inhalation Dusts and mists	Rat	0,11 mg/l	4 hours
	LC50 Inhalation Dusts and mists	Rat - Male, Female	0,5 mg/l	4 hours
	LD50 Oral	Rat - Male	490 mg/kg	-
4,5-dichloro-2-octyl-2H- isothiazol-3-one	LC50 Inhalation Dusts and mists	Rat	290 mg/m³	4 hours
	LD50 Oral	Rat	756 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
1,2-benzisothiazol-3(2H)-one	490	N/A	N/A	0,5	N/A
4,5-dichloro-2-octyl-2H-isothiazol-3-one	567	N/A	N/A	N/A	0,16

#### Irritation/Corrosion

**Conclusion/Summary** 

Zinsser Ceiling Pro 5-in-1

SECTION 11: Toxico	-		
Skin		,	tion criteria are not met.
Eyes		ilable data, the classifica	
Respiratory	: Based on ava	ilable data, the classifica	tion criteria are not met.
<u>Sensitisation</u>	-	_	
Product/ingredient name	Route of exposure	Species	Result
1,2-benzisothiazol-3(2H)-one	e skin	Guinea pig	Sensitising
Conclusion/Summary		I	
Skin	: Based on ava	ilable data, the classifica	tion criteria are not met.
Respiratory	: Based on ava	ilable data, the classifica	tion criteria are not met.
Mutagenicity		,	
Conclusion/Summary	: Based on ava	ilable data, the classifica	tion criteria are not met.
Carcinogenicity		,	
It has been observed that the leading to significant impairme Conclusion/Summary <u>Reproductive toxicity</u>	ent of particle clea		-
Conclusion/Summary	: Based on ava	ilable data, the classifica	tion criteria are not met.
Teratogenicity			
Conclusion/Summary	: Based on ava	ilable data, the classifica	tion criteria are not met.
Specific target organ toxicit	ty (single exposu	re)	
Not available.			
Specific target organ toxicit	ty (repeated expo	sure)	
Not available.		<u>(3010)</u>	
Aspiration hazard			
Not available.			
Information on likely routes		ry anticipated: Oral, Inha ry not anticipated: Derma	
Potential acute health effects	5		
Eye contact	: Slightly hazar	dous by the following rou	te of exposure: of eye contact (non-irritant)
Inhalation	: No known sig	nificant effects or critical	hazards.
Skin contact	: No known sig	nificant effects or critical	hazards.
Ingestion			hazards. However, in compliance with good o any chemical should be kept to a minimum
Symptoms related to the phy	vsical, chemical a	nd toxicological chara	<u>cteristics</u>
Eye contact	: No specific da	ita.	
	: No specific da	ita.	
Inhalation			
Inhalation Skin contact	: No specific da	ita.	
	<ul><li>No specific da</li><li>No specific da</li></ul>		
Skin contact Ingestion	: No specific da	ita.	and long-term exposure
Skin contact Ingestion <u>Delayed and immediate effec</u>	: No specific da	ita.	and long-term exposure
Skin contact	: No specific da	ita.	and long-term exposure
Skin contact Ingestion <u>Delayed and immediate effect</u> <u>Short term exposure</u> Potential immediate	: No specific da	ita.	<u>and long-term exposure</u>

## **SECTION 11: Toxicological information**

Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
<b>Conclusion/Summary</b>	: Based on available data, the classification criteria are not met.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards
11.2.1 Endocrine disrupting properties
Not available.
11.2.2 Other information
Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure	
1,2-benzisothiazol-3(2H)-one	Acute EC50 0,11 mg/l	Algae	72 hours	
	Acute EC50 0,067 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	
	Acute EC50 0,9893 mg/l Marine water	Crustaceans - Opossum Shrimp	96 hours	
	Acute EC50 2,94 mg/l Fresh water	Daphnia spec.	48 hours	
	Acute LC50 2,18 mg/l Fresh water	Fish	96 hours	
	Acute LC50 8 to 13 mg/l	Fish - Alburnus alburnus	96 hours	
	Acute LC50 1,6 to 2,8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours	
	Chronic NOEC 90 mg/l	Aquatic plants - Phaseolus vulgaris	20 days	
	Chronic NOEC 1,2 mg/l	Daphnia spec.	21 days	
	Chronic NOEC 0,21 mg/l	Fish	28 days	
	Chronic NOEL 0,0403 mg/l	Algae	72 hours	
4,5-dichloro-2-octyl-2H- isothiazol-3-one	Acute EC50 18 ppb Marine water	Algae - Skeletonema costatum	96 hours	
	Acute EC50 30,1 ppb Fresh water	Daphnia spec Daphnia magna	48 hours	
	Acute LC50 19,8 ppb Fresh water	Fish - Lepomis macrochirus	96 hours	

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### **12.2 Persistence and degradability**

Product/ingredient name	Test	Result		Dose	Inoculum
1,2-benzisothiazol-3(2H)-one	OECD 303A	>90 % - Readily - 1	days	-	-
<b>Conclusion/Summary</b> : This product has not been tested for biodegradation. Based on available data, the classification criteria are not met.					
Product/ingredient name	Aquatic half-life		Photolysis	5	Biodegradability
1,2-benzisothiazol-3(2H)-one	-		-		Readily

#### **12.3 Bioaccumulative potential**

Date of issue/Date of revision

Zinsser Ceiling Pro 5-in-1

## **SECTION 12: Ecological information**

Product/ingredient name	LogPow	BCF	Potential
1,2-benzisothiazol-3(2H)-one 4,5-dichloro-2-octyl-2H- isothiazol-3-one	0,64 3,59		low low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Nonvolatile liquid.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance.

#### 13.1 Waste treatment methods

#### Product

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Within the present knowledge of the supplier, this product is not regarded as

## **zardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

#### European waste catalogue (EWC)

Waste code	Waste designation
08 01 12	waste paint and varnish other than those mentioned in 08 01 11
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and

runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
Date of issue/Date of rev	/ision : 07/11/20	D22 Date of previous issue	: 07/11/2022	Version : 6 11/1

Zinsser Ceiling Pro 5-in-1

6					
SECTION 14: Transport information					
14.3 Transport hazard class(es)	-	-	-	-	
14.4 Packing group	-	-	-	-	
14.5 Environmental hazards	No.	No.	No.	No.	

14.6 Special precautions for user	:	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Transport in bulk	:	Not available.

according to INO	
instruments	

## **SECTION 15: Regulatory information**

5.1 Safety, health and envir Other EU regulations	onmen	tal regulations/legislation specific for the substance or mixture
voc		e provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the oduct label and/or technical data sheet for further information.
VOC for Ready-for-Use Mixture	pro	/a. Interior matt walls and ceilings (Gloss <25@60°). EU limit value for this oduct : 30g/l (2010.) is product contains a maximum of 4 g/l VOC.
Industrial emissions (integrated pollution prevention and control) - Air	: No	t listed
Industrial emissions (integrated pollution prevention and control) - Water	: No	t listed
United Kingdom: Great Bri	<u>ain</u>	
<u>UK (GB) /REACH</u>		
Annex XIV - List of substar	<u>ces sı</u>	ubject to authorisation
Annex XIV		
None of the components a	e listeo	d.
Substances of very high of	oncer	n
None of the components a	e listed	d.
Ozone depleting substance	s	
Not listed.	<u> </u>	
Prior Informed Consent (PI	<u>;)</u>	
Not listed.		
Persistent Organic Pollutat Not listed.	<u>its</u>	

## **SECTION 15: Regulatory information**

### Aerosol dispensers

#### Seveso Directive

This product is not controlled under the Seveso Directive.

÷

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

#### International regulations

#### Stockholm Convention on Persistent Organic Pollutants

List name	Ingredient name	Status
Not listed.		

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

List name			Ingredient name	Status	
Not listed.					
<b>CN code</b> : 3209 10 00	00				
Inventory list					
Australia	:	At least one co	omponent is not listed.		
Canada	1	At least one co	omponent is not listed.		
China	1	At least one co	omponent is not listed.		
<b>Eurasian Economic Union</b>	1	Russian Fede	ussian Federation inventory: Not determined.		
Japan	:	Japan inventory (CSCL): At least one component is not listed. Japan inventory (ISHL): Not determined.			
New Zealand	1	At least one co	omponent is not listed.		
Philippines	:	At least one component is not listed.			
Republic of Korea	:	Not determine	ot determined.		
Taiwan	:	At least one co	t least one component is not listed.		
Thailand	:	Not determined	d.		
Turkey	:	Not determined	Not determined.		
United States	:	Not determined.			
Viet Nam	:	Not determine	d.		
5.2 Chemical safety	:	This product co	ontains substances for which Chemical Safety A	ssessments are s	

assessment

This product contains substances for which Chemical Safety Assessments are still required.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration
-------------------------------	--

Date of issue/Date of revision	: 07/11/2022	Date of previous issue	:07/11/2022	Version	<b>:</b> 6	13/15
--------------------------------	--------------	------------------------	-------------	---------	------------	-------

Zinsser Ceiling Pro 5-in-1

#### SECTION 16: Other information RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] **Classification Justification** Not classified. Full text of abbreviated H statements **United Kingdom: Great Britain** Full text of abbreviated H ÷ H302 Harmful if swallowed. statements Causes severe skin burns and eye damage. H314 H315 Causes skin irritation. May cause an allergic skin reaction. H317 H318 Causes serious eye damage. H330 Fatal if inhaled. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. EUH071 Corrosive to the respiratory tract. Full text of classifications 2 Acute Tox. 2 ACUTE TOXICITY - Category 2 **ICLP/GHS1** Acute Tox. 4 ACUTE TOXICITY - Category 4 Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 Aquatic LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 Chronic 1 Aquatic LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 Chronic 2 Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 Skin Corr. 1 SKIN CORROSION/IRRITATION - Category 1 Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1 SKIN SENSITISATION - Category 1 Skin Sens. 1A SKIN SENSITISATION - Category 1A Date of printing : 07/11/2022

Date of issue/ Date of<br/>revision:::<th:</th><th:</th>:::<th:</th><th

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Zinsser Ceiling Pro 5-in-1

## **SECTION 16: Other information**

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.