

# **BLACKFRIAR PAINTS LTD**

## **TECHNICAL DATA SHEET**

### **BF038 Blackfriar QD Acrylic Primer Undercoat.**

Revision  
date:  
08/01/2007

<b><u>Product Information</u></b>	<b><u>Technical Spec</u></b>	<b><u>Recommended Spreading Rate</u></b>
<p><b><u>Description</u></b></p> <p>A quick drying primer/undercoat conforming to BS5082.</p>	<p><b><u>Composition</u></b></p> <p>A blend of selected pigments and extenders in an acrylic emulsion.</p>	<p>13m<sup>2</sup>/ltr</p>
<p><b><u>Usage/purpose</u></b></p> <p>Primarily formulated as a Primer/Undercoat for wood. May also be used as a primer undercoat over masonry, dry plaster, cement etc.</p>	<p><b><u>Properties</u></b></p> <p>VOC Content: 10-12 g/litre</p>	<p><b><u>Thinning</u></b></p> <p>Up to 10% with water</p>
<p><b><u>Characteristics</u></b></p> <p>A quick drying primer undercoat which gives good obliteration. Its fast drying properties mean that three coats of paint can be applied in a day under good conditions.</p>	<p><b><u>Performance</u></b></p> <p>Conforms to BS5082</p>	<p><b><u>Drying Time</u></b></p> <p>Touch dry in 1-2 hours Recoatable after 4 hours under normal conditions (20°C 50% r/h).</p>
<p><b><u>Finish</u></b></p> <p>Matt</p>	<p><b><u>Surface Preparation</u></b></p> <p>Ensure the substrate to be painted is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease etc). Ensure all knots are sealed with Blackfriar Patent Knotting.</p>	<p><b><u>Cleaning</u></b></p> <p>Clean application equipment or spills with Water</p>
<p><b><u>Colour(s)</u></b></p> <p>White (for overcoating with white and pastel shades) or Grey ( for colours).</p>	<p><b><u>Application Method</u></b></p> <p>Brush, Roller, Spray Ensure products are <u>thoroughly</u> stirred with a broad stirrer. Apply at least two full coats</p>	<p><b><u>Limitations</u></b></p> <p>Not suitable for use on metal surfaces – Use Blackfriar Metal Priming Paint or Blackfriar All Purpose Primer. Do not apply in cold (below 5°C) or damp/humid conditions.</p>
<p><b><u>Packaging</u></b></p> <p>250ml, 500ml, 1litre, 2.5litre 5 litres (white only). Larger sizes may be available on request dependent on volume required.</p>	<p><b><u>Disclaimer;</u></b> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p><b><u>Environmental Info.</u></b></p> <p>Water-Based.</p>
<p><b>For Technical information, Material Safety Data Sheets contact Sales on 0191 4106611</b></p>		<p><b>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</b></p>