

## DESCRIPTION

A water based matt emulsion paint specially formulated to resist mould growth for areas prone to intermittent damp conditions.

## RECOMMENDED USES



Suitable for interior use on new and aged plaster, wallboards, concrete, cement rendering, blockwork and brickwork. For use only in accordance with the directions on the tin.

## SPECIAL PROPERTIES

Anti-fungal (mould) film protection.

## COLOUR RANGE

Brilliant White; Magnolia.

## FINISH

Matt.

## VOLUME SOLID

23%

## COVERAGE



Johnstone's Stopmould will cover at the rate of approximately 9–11 square metres per litre, depending on the nature and porosity of the surface being painted.

## DRYING TIME



Touch dry in 1–2 hours.  
Recoat after 2–4 hours.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

## THINNER

Water.

## VOC CONTENT

LOW VOC CONTENT 0.30–7.99%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.  
EU limit value for this product (Cat A/i): 140g/l (2010).  
This product contains max 15g/l VOC.

## FILM THICKNESS

Wet: 100µm, dry: 25µm.

## SIZE

5 Litre.

## PREPARATION

Ensure the surface to be painted is clean, dry and free from loose or flaking matter. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Wear a suitable face mask when dry sanding. Surfaces already contaminated with mould growth should be treated with Johnstone's Sterilisation Wash as directed. For further advice contact Technical Advisory on 01924 354354.

## APPLICATION



Stir well before use. Suitable for application by brush, roller or spray. For spray application, or the first coat on porous surfaces, thin with up to 1 part water to 5 parts Johnstone's Stopmould. Do not apply when air or surface temperature is below 5°C.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

### Statutory conditions relating to use

- FOR USE ONLY AS A BIOCIDAL PAINT. APPLY AT A RATE OF ONE LITRE PER 9-11 SQUARE METRES OF SURFACE (DEPENDANT UPON SURFACE POROSITY) by brush, roller or spray.
- Wear suitable protective clothing and gloves.
- Do not breathe spray. Otherwise wear respiratory protective equipment and eye protection (See HSE guidance booklet HS (G) 53 "The Selection, Use and Maintenance of Respiratory Protective Equipment - A Practical Guide").
- Use only in well ventilated areas.
- KEEP AWAY FROM TREATED SURFACES UNTIL DRY.
- DO NOT CONTAMINATE FOODSTUFFS, EATING UTENSILS OR FOOD CONTACT SURFACES.
- Do not empty into drains.
- DO NOT USE NEAR DRAINS. PREVENT ANY SURFACE RUN-OFF FROM ENTERING DRAINS.
- REMOVE OR COVER ALL FISH TANKS AND BOWLS before application.
- COVER WATER STORAGE TANKS before application.
- This material and its container must be disposed of in a safe way.
- DANGEROUS TO FISH AND OTHER AQUATIC LIFE.
- Do not contaminate ground or watercourses with chemicals or used container.
- READ ALL PRECAUTIONS BEFORE USE (HSE No. 7363)
- WASH ANY CONTAMINATION from skin and eyes immediately.
- WASH HANDS AND EXPOSED SKIN before meals and after use.
- Keep only in original container.
- Keep container tightly closed.
- KEEP IN A SAFE PLACE.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.

CONTAINS:- DICHLOROPHENYL DIMETHYLUREA 0.10% W/W  
CABENDAZIM 0.045% W/W 2-OCTYL-2H-ISOTHIAZOL-3-ONE 0.014% W/W

This product is approved under The Control of Pesticides Regulations 1986 for use as directed. HSE No. 7363